




### Benefits

- ▶ 1U 19" widescreen LCD Quad display drawer
- ▶ 1440 x 900 native resolution / 16.7M colors
- ▶ VGA + Quad Display ( Composite BNC x 4 ) video input
- ▶ One Man installation design
- ▶ Enhanced aesthetics with molded front panel and two point lock
- ▶ 2-year standard warranty ( upgradable up to 5 years )

### Options

- DC power : 12V / 24V / 48V / 125V

### RP-W119QD



## Product Specifications

Video	
Video input	QD ( Composite BNC x 4 ) + VGA

LCD Panel	
Panel size ( diagonal )	19"
Native resolution	1440 x 900
Brightness ( cd/m <sup>2</sup> )	300
Contrast ratio ( typ. )	1000 : 1
Colors	16.7 M
Viewing angle ( L/R/U/D )	80/80/80/80
Response time ( ms )	5
Dot pitch ( mm )	0.2835
Display area ( mm )	408.24H x 255.15V
Surface treatment	Haze 25%, Hard-coating
Surface hardness	3H
Backlight type	CCFL
MTBF (hrs)	50,000

Power		
Input	Auto-sensing 100 to 240VAC, 50 / 60Hz	
Consumption	Screen on	Max. 25W
	Power saving mode	Max. 4W
	Power button on	Max. 1W

Environment	
Operating temp.	0 to 55°C degree
Storage temp.	-20 to 60°C degree
Operating humidity	20~90%, non-condensing
Storage humidity	5 ~90%, non-condensing
Operating altitude	16,000 ft
Non-operating altitude	40,000 ft
Shock	10G acceleration ( 11ms duration )
Vibration	10~300Hz 0.5G RMS random vibration

Compliance	
EMC	FCC & CE certified
Safety	CE / LVD certified
Environment	RoHS2 & REACH compliant

Mounting Distance	
Display drawer	660 ~ 890 mm 26 ~ 35 inch

Physical		
Dimensions ( W x D x H )	Product	445 x 650 x 44 mm 17.5 x 25.6 x 1.73 inch
	Packing	595 x 860 x 140 mm 23.4 x 33.9 x 5.5 inch
Weight	Net	13.5 kg / 29.7 lb
	Gross	17.5 kg / 38.5 lb

### Diagrams ( mm )

